



| # | DETAIL | DESCRIPTION |
|----|--------------|---|
| 1 | DISPLAY | AF-3550-80 X 64-16MM |
| 2 | LED COLOR | RGB |
| 3 | ACTIVE AREA | 4' 4-1/4" [1327] X 3' 5-5/8" [1057] |
| 4 | OVERALL SIZE | 4' 11-5/8" [1514] X 3' 11-11/16" [1212] |
| 5 | CABINET | ALUMINUM, PAINTED SEMI-GLOSS BLACK |
| 6 | VENTILATION | INTAKE & EXHAUST AT BOTTOM-FRONT |
| 7 | ACCESS | SERVICE FROM FRONT ONLY |
| 8 | WEIGHT | 170 LBS [77 KG] (APPROX) |
| 9 | SHIPPING | SHIPPED & INSTALLED AS SINGLE UNIT |
| 10 | DIMENSIONS | FEET AND INCHES [MILLIMETERS] |

| STRUCTURAL RATING | |
|-------------------|-------------------------------------|
| 1 | DESIGN WIND PRESSURE "P" P<=110 PSF |
| 2 | STANDARD/CODE IBC 2006 |

| # | COLOR | EFFECTIVE DATE | WATTS | DOMESTIC | | | INTERNATIONAL |
|---|-------|------------------|-------|---------------------------|---------------|------------------------------|---------------|
| | | | | 120VAC, 60Hz 2 WIRE + GND | | 240VAC, 1PH 50Hz 2WIRE + GND | |
| | | | | LINE 1 (AMPS) | LINE 2 (AMPS) | LINE 1 (AMPS) | |
| 1 | RGB | AFTER 4/26/12 | 790 | 6.58 | N/A | N/A | 3.29 |
| 2 | RGB | PRIOR TO 4/25/12 | 1040 | 8.67 | N/A | N/A | 4.33 |

- INSTALL NOTES**
- DISPLAY IS FRONT VENTILATED SO NO PORTION OF THE FRONT FACE CAN BE COVERED. AIR INTAKES ARE FILTERED. FILTERS ARE LOCATED IN DRAWERS ON FACE AND WILL NEED TO BE PERIODICALLY CLEANED TO ENSURE PROPER VENTILATION. REFER TO MAINTENANCE DOCUMENT (DD-1564079) FOR FILTER MAINTENANCE INSTRUCTIONS.
 - IN ORDER TO MAINTAIN THE STRUCTURAL INTEGRITY OF THE DISPLAY CABINET, USE SPREADER BEAM AND MAINTAIN A 90° ANGLE BETWEEN THE CABINET AND THE LIFTING METHOD. ALL EYEBOLTS MUST BE USED FOR LIFTING THE CABINET.
 - 1/2" EYEBOLTS TO ASSIST WITH DISPLAY INSTALLATION. EYEBOLTS MAY BE REMOVED AFTER INSTALLATION.
 - EYEBOLTS MAY NOT BE USED FOR PERMANENT INSTALLATION.
 - L3X3X3/8" X3 WIDE" ASTM A36 STEEL ANGLE FOR MOUNTING ATTACHED TO THE DISPLAY WITH 1/2" BOLT AND NUT INSERT. CLIP ANGLE CAN BE ADJUSTED VERTICALLY AS NEEDED DURING INSTALLATION.
 - DAKTRONICS IS NOT RESPONSIBLE FOR THE MOUNTING HARDWARE OR THE INTEGRITY OF THE STRUCTURE TO WHICH THE DISPLAY IS MOUNTED TO.
 - EXTERNAL JUNCTION BOX IS PROVIDED FOR POWER TERMINATION. SEE POWER RATINGS ABOVE.
 - SIGNAL INPUT AT QUICK CONNECT. PRIMARY/SINGLE FACE DISPLAY SHOWN. SEE CLEARANCE DIMENSION ON DETAIL VIEW B.
 - SIGNAL OUTPUT QUICK CONNECT FOR MIRROR FACE.
 - GROUND LUG FOR GROUND LUG CONNECTION. DISPLAY NEEDS TO BE GROUNDED.
 - TWO 1/2" CONDUIT KNOCKOUT LOCATIONS FOR OPTIONAL SIGNAL ENTRANCE
 - DAKTRONICS IS NOT RESPONSIBLE FOR THE MAIN ELECTRICAL DISCONNECT.

SUBMITTAL APPROVAL

APPROVED

APPROVED AS NOTED

APPROVED AS NOTED & RESUBMIT

COMPANY: _____

SIGNED: _____

TITLE: _____ DATE: _____

| | | | |
|---------------------------------------|----------------|--|----------------------------|
| DAKTRONICS, INC. | | THE CONCEPTS EXPRESSED AND DETAILS SHOWN ON THIS DRAWING ARE CONFIDENTIAL AND PROPRIETARY. DO NOT REPRODUCE BY ANY MEANS WITHOUT THE EXPRESSED WRITTEN CONSENT OF DAKTRONICS, INC. COPYRIGHT 2013 DAKTRONICS, INC. | |
| BROOKINGS, SD 57006 | | DO NOT SCALE DRAWING | |
| PROJ: GALAXY AF-3550 16MM DISPLAYS | | | |
| TITLE: SHOP DWG, AF-3550-80X64-16-RGB | | | |
| DESIGN: TWHITEH | DRAWN: RBJERKE | DATE: 30-MAY-13 | |
| SCALE: 1=30 | | | |
| SHEET: 1 OF 1 | REV: 01 | JOB NO: P 1569 | FUNC-TYPE-SIZE: E - 07 - B |
| | | | 1046039 |

| | | | |
|-----|-----------|----------------------------|-----|
| 01 | 30 MAY 13 | UPDATED POWER REQUIREMENTS | KMA |
| REV | DATE: | | BY: |