

THIS IS A SINGLE FACED DROP-IN DISPLAY TO BE MOUNTED IN A RECTANGULAR OPENING IN A LARGER SIGN.

DIMENSIONS ARE IN INCHES [MILLIMETERS].

USE HOLES IN THE FRONT FLANGES OF THE CABINET TO ATTACH THE DISPLAY TO THE SIGN FACE USING APPROPRIATE HARDWARE.

DAKTRONICS IS NOT RESPONSIBLE FOR THE MOUNTING STRUCTURE OR FOR THE ADEQUACY OF ATTACHMENT TO THE STRUCTURE. STRUCTURE AND ATTACHMENT MUST CONFORM TO ALL APPLICABLE BUILDING CODES.


THE OVERALL SIGN STRUCTURE MUST BE DESIGNED WITH SUFFICIENT VENTILATION SO THAT AIR AROUND THE DISPLAY DOES NOT EXCEED 120°F [49°C].

THE DISPLAY IS FRONT VENTILATED. NO PORTION OF THE FACE MAY BE COVERED.

SIGNAL INTERCONNECT CABLES ARE PROVIDED AND MUST BE ROUTED AND CONNECTED WHEN MULTIPLE DISPLAYS ARE INSTALLED WITHIN A SINGLE SIGN.

THIS DISPLAY IS A UL RECOGNIZED COMPONENT.

REFER TO THE DISPLAY MANUAL FOR COMMUNICATION OPTIONS AND INSTALLATION INSTRUCTIONS.



FEATURE					
DIGIT HEIGHT	24" [610 MM]				
DIGIT LED COLOR	RED, AMBER, OR GREEN				
CABINET COLOR	SEMI-GLOSS BLACK				
SERVICE ACCESS	FRONT ONLY				
CABINET MATERIAL	0.063 [1.6] ALUMINUM SHEET				
EST. WEIGHT	45 LB [21 KG]				
MAX OPER. TEMP.	120°F [49°C]				
PRIMARY VOLTS	100V - 240V AC				
MAX. POWER	110 W				
PRIMARY VOLTS	100V - 240V AC				

						CIRONIC BROOKINGS,	,	THIS DRAWING ARE COI DO NOT REPRODUCE B	SSED AND DETAILS SHOWN ON NFIDENTIAL AND PROPRIETARY. Y ANY MEANS WITHOUT THE
03	08 MAY 13 REVISED TEMPERATURE RATING.	REVISED TEMPERATURE RATING.	AVB		DO NOT SCALE DRAWING EXPRESSED WRITTEN CONSENT OF DAKTROIC COPYRIGHT 2011 DAKTRONICS, INC.				
				PROJ: FUELIGHT DISPLAYS					
02	12 OCT 12	INCREASED NO. OF MOUNTING HOLES IN HORIZ. FLANGES PER EC-7618.	AVB		TITLE: SHOP DRA				
	05 JUN 12 UPDATED WEIGHT.	AVB		DESIGN: A VANB	EMMEL	DRAWN: A VAI	NBEMMEL	DATE: 07-MAY-13	
01			·	SCALE: 4/100					
	DATE: B			SHEET:	REV	JOB NO:	FUNC-TYPE-SIZE	1086412	
REV		BY:		1 OF 1	03	P 1611	R = 08 = A	1000412	

DAKEDONIOO INO