

THIS IS A SINGLE FACED DROP-IN DISPLAY TO BE MOUNTED IN A RECTANGULAR OPENING IN A LARGER SIGN.

DIMENSIONS ARE IN INCHES [MILLIMETERS].

USE HOLES IN THE FRONT FLANGES OF THE CABINET TO ATTACH THE DISPLAY TO THE SIGN FACE USING APPROPRIATE HARDWARE.

DAKTRONICS IS NOT RESPONSIBLE FOR THE MOUNTING STRUCTURE OR FOR THE ADEQUACY OF ATTACHMENT TO THE STRUCTURE. STRUCTURE AND ATTACHMENT MUST CONFORM TO ALL APPLICABLE BUILDING CODES.


THE OVERALL SIGN STRUCTURE MUST BE DESIGNED WITH SUFFICIENT VENTILATION SO THAT AIR AROUND THE DISPLAY DOES NOT EXCEED 120°F [49°C].

THE DISPLAY IS FRONT VENTILATED. NO PORTION OF THE FACE MAY BE COVERED.


SIGNAL INTERCONNECT CABLES ARE PROVIDED AND MUST BE ROUTED AND CONNECTED WHEN MULTIPLE DISPLAYS ARE INSTALLED WITHIN A SINGLE SIGN.

THIS DISPLAY IS A UL RECOGNIZED COMPONENT.

REFER TO THE DISPLAY MANUAL FOR COMMUNICATION OPTIONS AND INSTALLATION INSTRUCTIONS.



FEATURE	
DIGIT HEIGHT	24" [610 MM]
DIGIT LED COLOR	RED, AMBER, OR GREEN
CABINET COLOR	SEMI-GLOSS BLACK
SERVICE ACCESS	FRONT ONLY
CABINET MATERIAL	0.063 [1.6] ALUMINUM SHEET
EST. WEIGHT	45 LB [21 KG]
MAX OPER. TEMP.	120°F [49°C]
PRIMARY VOLTS	100V - 240V AC
MAX. POWER	110 W

 DAKTRONICS, INC. BROOKINGS, SD 57006 DO NOT SCALE DRAWING	THE CONCEPTS EXPRESSED AND DETAILS SHOWN ON THIS DRAWING ARE CONFIDENTIAL AND PROPRIETARY. DO NOT REPRODUCE BY ANY MEANS WITHOUT THE EXPRESSED WRITTEN CONSENT OF DAKTRONICS, INC. COPYRIGHT 2011 DAKTRONICS, INC.		
	PROJ: FUELIGHT DISPLAYS TITLE: SHOP DRAWING, FL-4500-24-DI		
DESIGN: A VANBEMMEL	DRAWN: A VANBEMMEL	DATE: 07-MAY-13	
SCALE: 4/100			
SHEET: 1 OF 1	REV: 02	JOB NO: P 1611	FUNC-TYPE-SIZE: R - 08 - A
			1086421

REV	DATE	DESCRIPTION	BY
02	08 MAY 13	REVISED TEMPERATURE RATING	AVB
01	12 NOV 12	INCREASED NO. OF MOUNTING HOLES IN HORIZ. FLANGES PER EC-7618.	AVB