

THIS IS A SINGLE FACED DISPLAY, BUILT IN TWO SECTIONS WITH DIMENSIONS AS SHOWN ABOVE. THE DISPLAY MAY BE MOUNTED IN ONE OF TWO WAYS: AS A COMPONENT OF A LARGER SIGN, OR MOUNTED INDEPENDENTLY, DIRECTLY TO A STRUCTURE.

DAKTRONICS IS NOT RESPONSIBLE FOR THE MOUNTING STRUCTURE OR FOR THE ADEQUACY OF ATTACHMENT TO THE STRUCTURE. STRUCTURE AND ATTACHMENT MUST CONFORM TO ALL APPLICABLE BUILDING CODES.

DIMENSIONS ARE IN INCHES [MILLIMETERS].

THE OVERALL SIGN STRUCTURE MUST BE DESIGNED WITH SUFFICIENT VENTILATION SO THAT AIR AROUND THE DISPLAY DOES NOT EXCEED 120°F [49°C].

THE DISPLAY IS FRONT VENTILATED. NO PORTION OF THE FACE MAY BE COVERED.

SIGNAL INTERCONNECT CABLES ARE PROVIDED AND MUST BE ROUTED AND CONNECTED WHEN MULTIPLE DISPLAYS ARE INSTALLED WITHIN A SINGLE SIGN.

REFER TO THE DISPLAY MANUAL FOR COMMUNICATION OPTIONS AND INSTALLATION INSTRUCTIONS.

FEATURE	
DIGIT HEIGHT	36" [914 MM]
DIGIT LED COLOR	RED, AMBER, OR GREEN
CABINET COLOR	SEMI-GLOSS BLACK
SERVICE ACCESS	FRONT ONLY
CABINET MATERIAL	0.063 [1.6 MM] ALUMINUM SHEET
EST. WEIGHT	100 LB [45 KG]
MAX. OPER. TEMP.	120°F [49°C]
PRIMARY VOLTS	100V - 240V AC
MAX. POWER	270 W

