

THIS IS A SINGLE FACED DROP-IN DISPLAY TO BE MOUNTED IN A RECTANGULAR OPENING IN A LARGER SIGN.

DIMENSIONS ARE IN INCHES [MILLIMETERS].

USE HOLES IN THE FRONT FLANGES OF THE CABINET TO ATTACH THE DISPLAY TO THE SIGN FACE USING APPROPRIATE HARDWARE.

DAKTRONICS IS NOT RESPONSIBLE FOR THE MOUNTING STRUCTURE OR FOR THE ADEQUACY OF ATTACHMENT TO THE STRUCTURE. STRUCTURE AND ATTACHMENT MUST CONFORM TO ALL APPLICABLE BUILDING CODES.

THE OVERALL SIGN STRUCTURE MUST BE DESIGNED WITH SUFFICIENT VENTILATION SO THAT AIR AROUND THE DISPLAY DOES NOT EXCEED 120°F [49°C].

THE DISPLAY IS FRONT VENTILATED. NO PORTION OF THE FACE MAY BE COVERED.

SIGNAL INTERCONNECT CABLES ARE PROVIDED AND MUST BE ROUTED AND CONNECTED WHEN MULTIPLE DISPLAYS ARE INSTALLED WITHIN A SINGLE SIGN.

THIS DISPLAY IS A UL RECOGNIZED COMPONENT.

REFER TO THE DISPLAY MANUAL FOR COMMUNICATION OPTIONS AND INSTALLATION INSTRUCTIONS.



FEATURE		
DIGIT HEIGHT	20" [508 MM]	
DIGIT LED COLOR	RED, AMBER, OR GREEN	
CABINET COLOR	SEMI-GLOSS BLACK	
SERVICE ACCESS	FRONT ONLY	
CABINET MATERIAL	0.063 [1.6] ALUMINUM SHEET	
EST. WEIGHT	40 LB [18 KG]	
MAX. OPER. TEMP.	120°F [49°C]	
PRIMARY VOLTS	100V - 240V AC	
MAX. POWER	100 W	
MAX. OPER. TEMP. PRIMARY VOLTS	120°F [49°C] 100V - 240V AC	

THE CONCEPTS EXPRESSED AND DETAILS SHOWN ON THIS DRAWING ARE CONPICIONAL AND PROPRIETARY. DO NOT REPRODUCE BY ANY MEANS WITHOUT THE EXPRESS WRITTEN CONSENT OF DAKTRONICS, INC. OR ITS WHOLLY OWNED SUBSIDIARIES. COPYRIGHT 2016 DAKTRONICS, INC. (USA)							JECTION			
	PROJECT:	PROJECT: FUELIGHT DISPLAYS								
	TITLE:	SHOP DRAWIN	OP DRAWING, FL-3000-20-DI							
	DATE:	22-OCT-15	DIM UNITS:	INCHES [MILLIMETE	RS]	SHEET	REV			
	SCALE:	1/20	DO NO	OT SCALE DRAWING	}	1 OF 1	00			
	DESIGN:	A VANBEMMEL	JOB NO.	FUNC - TYPE - SIZE	2	1776	11			
	DRAWN:	A VANBEMMEL	P1611	R - 08 - A	<u> </u>	1770	44			