



#	DETAIL	DESCRIPTION				
1	DISPLAY	GT6 - 180 x 468 - 10				
2	LED COLOR	RGB				
3	ACTIVE AREA	6' [1829] X 15' 7-3/16" [4754]				
4	OVERALL SIZE	6' 6-1/16" [1983] X 15' 10-3/16" [4831]				
5	CABINET	ALUMINUM & STEEL				
6	VENTILATION	FRONT				
7	ACCESS	SERVICE FROM FRONT OF DISPLAY				
8	WEIGHT	977 LBS [444 KG] (APPROX)				
9	SHIPPING	SHIPPED AS A SINGLE UNIT				
10	DIMENSIONS	FEET AND INCHES [MILLIMETERS]				
11	PAINTED	SEMI-GLOSS BLACK				
STRUCTURAL RATING						
1	DESIGN WIND PRESSURE "P" (CASE A)	P<=:100 PSF (ASD)				
2	STANDARD/CODE	IBC 2009/ASCE7-05, IBC 2012/ASCE7-10				
3	ALL CLIP ANGLES MUST BE USED TO MOUNT DISPLAY					
POWER RATING PER SINGLE FACE: FOR SIZING ELEC.SERVICE MAX REQ'D SHOWN						
TECHNOLOGY	COLOR	MAX WATTS	120 VAC 1 PH 50/60 HZ AMPS	120/240 VAC1PH 50/60Hz (3 WIRES+GND)		240VAC 1PH 50Hz (2 WIRES + GND)
				LINE 1 (AMPS)	LINE 2 (AMPS)	
GT6	RGB	5939	N/A	23.99	225.28	SPECIAL ORDER
VENTILATION REQUIREMENTS						
1	DISPLAY RELIES ON VENTILATION TO FUNCTION PROPERLY. INTAKES, LOCATED AT THE FRONT OF THE DISPLAY, MUST BE ABLE TO DRAW IN AIR AT A TEMPERATURE NO GREATER THAN 120° F.					
2	IN ORDER TO ENSURE AMBIENT TEMPERATURE AIRFLOW IS MAINTAINED, NO PORTION OF THE VENTILATION OPENINGS ALONG THE FRONT OF THE DISPLAY MAY BE COVERED OR OBSTRUCTED IN ANY WAY.					
INSTALL NOTES						
1	IN ORDER TO PRESERVE THE STRUCTURAL INTEGRITY OF THE DISPLAY CABINET, THE 90° ANGLE BETWEEN THE CABINET AND THE LIFTEYE MUST BE MAINTAINED - USING A SPREADER BEAM IS SUGGESTED. ALL EYEBOLTS MUST BE USED WHEN LIFTING.					
2	1/2" LIFTEYES TO ASSIST WITH DISPLAY INSTALLATION. LIFTEYES MAY NOT BE USED FOR PERMANENT INSTALLATION. LIFTEYES MAY BE REMOVED.					
3	MECHANICAL AND SIGNAL CONNECTIONS OCCUR EXTERNAL TO DISPLAY.					
4	CLIP ANGLE FOR MOUNTING. CLIP ANGLES CAN BE ADJUSTED VERTICALLY DURING INSTALLATION. CLIP ANGLE CAN BE WELDED OR BOLTED TO STRINGER. ALL CLIP ANGLE LOCATIONS MUST BE USED.					
5	DAKTRONICS IS NOT RESPONSIBLE FOR THE MOUNTING HARDWARE OR THE INTEGRITY OF THE MOUNTING STRUCTURE.					
6	DAKTRONICS IS NOT RESPONSIBLE FOR THE MAIN ELECTRICAL DISCONNECT. SEE POWER RATINGS ABOVE.					
7	SEE DWG-03891140 FOR SIGNAL & MTG DETAILS					

01	17 MAY 19	PER CN-79899: CHANGED 240VAC TO SPECIAL ORDER	EJW 20020	
REV	DATE:		BY:	
<div><div></div><div>THE CONCEPTS EXPRESSED AND DETAILS SHOWN ON THIS DRAWING ARE CONFIDENTIAL AND PROPRIETARY. DO NOT REPRODUCE BY ANY MEANS WITHOUT THE EXPRESS WRITTEN CONSENT OF DAKTRONICS, INC. OR ITS WHOLLY OWNED SUBSIDIARIES. COPYRIGHT 2018 DAKTRONICS, INC. (USA)</div></div> <div>THIRD ANGLE PROJECTION</div>				
PROJECT: GT6 DISPLAYS				
TITLE: SHOP DWG, GT6, 6' 6"x15' 11" (5x13 MODS)				
DATE: 16-MAY-19	DIM UNITS: INCHES [MILLIMETERS]			SHEET 1 OF 1
SCALE: 1/30	DO NOT SCALE DRAWING			REV 01
DESIGN: TWHITEH	JOB NO.	FUNC - TYPE - SIZE	4034187	
DRAWN: BDRAKE	P2056	E - 07 - B		